


**STANDARD DEPARTURE CHART -
INSTRUMENT (SID) - ICAO**

Transition Altitude 9 000 ft

DEP 123.8

HONG KONG INTERNATIONAL
RNAV_(GNSS) LAKES 2B SID (RWY 25L)
RNAV_(GNSS) LAKES 2D SID (RWY 25R)

1. Aircraft that do not have RNP1/P-RNAV approval or whose RNP1/P - RNAV capability has been degraded before departure shall use the conventional departure procedure as described below.
2. PRAWN is a **FLY-OVER** waypoints. All other waypoint are fly-by.
3. Carriage of certified GNSS receiver is mandatory for this procedure.
4. (DER) - Departure End of Runway.

**RWY 25L - LAKES 2B****RNP1/P-RNAV Departure Procedure**

(Only available to aircraft appropriately equipped and approved)

PRAWN[K230;-L] - RUMSY[L] - TUNNA[L] - TROUT[L] - LAKES

CLIMB INSTRUCTIONS

Initial climb to 5 000 ft. Expect further climb when instructed by ATC. Cross TROUT FL140 or above.

TERRAIN CLEARANCE

Minimum climb gradient of 3.3% (201 ft/NM).

SPEED RESTRICTION

Speed restriction of 230 kt IAS maximum until established on track to RUMSY.

Conventional Departure Procedure

(For all other aircraft)

Track 253°M to PRAWN (IFL DME 7.0 NM, or crossing LKC DVOR RDL 214). At PRAWN turn left track 184°M to intercept NLG DVOR RDL 155 at RUMSY. From RUMSY turn left direct to TUNNA then turn left direct to TROUT and then turn left direct to LAKES. After LAKES continue flight plan V1 route.

If NLG DVOR is not available, at PRAWN turn left to track 184°M, request radar vectors to TUNNA.

CLIMB INSTRUCTIONS

Initial climb to 5 000 ft. Expect further climb when instructed by ATC. Cross TROUT FL140 or above.

TERRAIN CLEARANCE

Minimum climb gradient of 3.3% (201ft/NM).

SPEED RESTRICTION

Speed restriction of 230 kt IAS maximum until established on track to RUMSY.

RWY 25R - LAKES 2D**RNP1/P-RNAV Departure Procedure**

(Only available to aircraft appropriately equipped and approved)

RWY25R(DER) - PRAWN[K230;-L] - RUMSY[L] - TUNNA[L] - TROUT[L] - LAKES

CLIMB INSTRUCTIONS

Initial climb to 5 000 ft. Expect further climb when instructed by ATC. Cross TROUT FL140 or above.

TERRAIN CLEARANCE

Minimum climb gradient of 3.3% (201ft/NM).

SPEED RESTRICTION

Speed restriction of 230 kt IAS maximum until established on track to RUMSY.

Conventional Departure Procedure

(For all other aircraft)

Track 253°M to PRAWN (ITFR DME 3.0 NM, or crossing LKC DVOR RDL 214). At PRAWN turn left track 184°M to intercept NLG DVOR RDL 155 at RUMSY. From RUMSY turn left direct to TUNNA then turn left direct to TROUT and then turn left direct to LAKES. After LAKES continue flight plan V1 route.

If NLG DVOR is not available, at PRAWN turn left to track 184°M, request radar vectors to TUNNA.

CLIMB INSTRUCTIONS

Initial climb to 5 000 ft. Expect further climb when instructed by ATC. Cross TROUT FL140 or above.

TERRAIN CLEARANCE

Minimum climb gradient of 3.3% (201ft/NM).

SPEED RESTRICTION

Speed restriction of 230 kt IAS maximum until established on track to RUMSY.